



200 SF 15W50



German Quality

MUXX OIL GmbH
15 Frankenhauser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- Mineral Passenger Car Motor Oil
- E 200 SF 15W50 is a multi-functional mineral engine oil for older gasoline-, diesel- and LGP engines of passenger cars and light vans with or without turbo compressor.
- E 200 SF 15W50 is formulated on high performance virgin base oils in combination with selected additive package to reach the following properties:
 - Stable viscosity index.
 - Good protection against rust, corrosion and wear.
 - Good dispersancy and detergency properties.
 - Good antifoam properties.

Performance Levels

API SF/CD

Test Item	Typical Spec.	Typical Result
SAE Grade		15W50
Density @15°C	kg/m ³	897
Kin. Viscosity @40°C	mm ² /s	155
Kin. Viscosity @100°C	mm ² /s	17.5
Viscosity Index		145
Viscosity CCS @-20°, max.	cP	7000
Flash Point COC	°C	>201
Pour Point	°C	-27
Total Base Number	mgKOH/g	4.9
Sulphated Ash	%Wt	0.7

*The Above Test Result is subject for change and for reference only



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

