



German Quality

MUXX OIL GmbH
 15 Frankenhauer St., 12249 Berlin,
 Germany.
 Office: +49 (0)30 61633942
 Website: www.muxxlube.de
 E-Mail: service@muxxlube.com

Description

- E 200 SL 10W40 is manufactured from high quality refined base oil and an advanced additive. It is designed primarily for petrol engines, but it may be used in older version of diesel engines as well. E 200 SL 10W40 keeps engine components clean and deposit free. It also provides protection against wear, rust and corrosion. This grade is ideal for engines suffering from high oil consumption or reduced (low) oil pressure.
- E 200 SL 10W40 is recommended for passenger cars and light duty diesel engines. E 200 SL 10W40 common viscosity range is ideal for vehicles which require quick oil flow performance in certain weather conditions. It can be used for most OEMs car manufacture without any emission requirement

Performance Levels

API SL/CF

Test Item	Typical Spec.	Typical Result
SAE Grade		10W40
Density @15°C	kg/m ³	852
Kin. Viscosity @40°C	mm ² /s	103.77
Kin. Viscosity @100°C	mm ² /s	14.92
Viscosity Index		147
Viscosity CCS @-25°, max.	cP	6300
Flash Point COC	°C	228
Pour Point	°C	-30
Total Base Number	mgKOH/g	7.0
Color		L2.0

*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE
 LUBRICANTS QUALITY
 MANAGEMENT SYSTEM

