



German Quality

MUXX OIL GmbH  
 15 Frankenhauser St., 12249 Berlin,  
 Germany.  
 Office: +49 (0)30 61633942  
 Website: [www.muxxlube.de](http://www.muxxlube.de)  
 E-Mail: [service@muxxlube.com](mailto:service@muxxlube.com)

## Description

- Mineral Passenger Car Motor Oil
- E 200 SL 15W40 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.
- E 200 SL 15W40 is based on high performance virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties:
  - Good thermal and oxidation stability.
  - Stay-in-grade.
  - Good protection against wear, foam and corrosion.
  - Low temperature properties, to ensure a smooth cold start.

## Performance Levels

API SL/CF

ACEA A3/B3

VW 505.00

MB 229.1

Test Item	Typical Spec.	Typical Result
SAE Grade		15W40
Density @15°C	kg/m <sup>3</sup>	881
Kin. Viscosity @40°C	mm <sup>2</sup> /s	105
Kin. Viscosity @100°C	mm <sup>2</sup> /s	14.1
Viscosity Index		134
Viscosity CCS @-25°, max.	cP	7000
Flash Point COC	°C	220
Pour Point	°C	-33
Total Base Number	mgKOH/g	7.9
Sulphated Ash	%Wt	0.96

\*The Above Test Result is subject for change and for reference only



**EELQMS**  
 EUROPEAN ENGINE  
 LUBRICANTS QUALITY  
 MANAGEMENT SYSTEM

