

- Synthetic Heavy Duty Diesel Engine Oil
- H 600 3477 10W40 is a fuel conserving super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year and running on low Sulphur Diesel Fuel (max. 50 ppm).
- H 600 3477 10W40 is formulated for use in Euro-4, Euro-5 and Euro-6 engines equipped with Diesel Particle Filter (DPF). This product is also suitable for vehicles equipped with EGR and/or SCR after treatment systems.

## **Performance Levels**

	t. 14		Turing Course	Transienel Descult	
Vc	olvo VDS-3	MACK EO-N	Deutz DQC	-III-10-LA MT	U Type 3.1
AF	PI CI-4	ACEA E6/E7	MB 228.51	MAN M 34	77 Renault VI RLD-2

Test Item	Typical Spec.	Typical Result
SAE Grade		10W40
Density @15°C	kg/m3	863
Kin. Viscosity @40°C	mm2/s	89
Kin. Viscosity @100°C	mm2/s	13.9
Viscosity Index		145
Viscosity CCS @-25°, max.	cP	7000
Flash Point COC	°C	210
Pour Point	°C	-36
Total Base Number	mgKOH/g	10.2
Sulphated Ash	%Wt	0.8





\*The Above Test Result is subject for change and for reference only

