



# 600 0W30



German Quality

MUXX OIL GmbH  
15 Frankenhauser St., 12249 Berlin,  
Germany.  
Office: +49 (0)30 61633942  
Website: [www.muxxlube.de](http://www.muxxlube.de)  
E-Mail: [service@muxxlube.com](mailto:service@muxxlube.com)

## Description

- Fully Synthetic Passenger Car Motor Oil
- X 600 0W30 is a fuel saving oil based on 100% synthetic technology specially designed for use in petrol and diesel powered Volvo passenger cars with or without turbocharger where Volvo VCC 95200377 is required.
- X 600 0W30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:
  - Protection to wear by cold start.
  - Very good low temperature properties.
  - Very high thermal- and oxidation stability.
  - Excellent resistance against foaming, corrosion and wear.
  - High dispersancy and detergency level.
  - High viscosity index.
  - Added fuel economy

## Performance Levels

API SN/SM/CF   ACEA A1/B1-12   ACEA A5/B5-12   ACEA C2-12   Renault RN0700

Test Item	Typical Spec.	Typical Result
SAE Grade		0W30
Density @15°C	kg/m <sup>3</sup>	843
Kin. Viscosity @40°C	mm <sup>2</sup> /s	51
Kin. Viscosity @100°C	mm <sup>2</sup> /s	9.6
Viscosity Index		165
Viscosity CCS @-30°, max.	cP	6200
Flash Point COC	°C	>201
Pour Point	°C	-42
Total Base Number	mgKOH/g	9.2
Sulphated Ash	%Wt	1.0

\*The Above Test Result is subject for change and for reference only



**EELQMS**  
EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

