



# 600 5W40



German Quality

MUXX OIL GmbH  
15 Frankenhauser St., 12249 Berlin,  
Germany.  
Office: +49 (0)30 61633942  
Website: [www.muxxlube.de](http://www.muxxlube.de)  
E-Mail: [service@muxxlube.com](mailto:service@muxxlube.com)

## Description

-Fully Synthetic Passenger Car Motor Oil  
-X 600 5W40 is a modern 100% PAO synthetic technology engine oil for use in high output, turbocharged, supercharged multi valve fuel injected engines in passenger cars, SUVs and light vans.  
-X 600 5W40 is formulated with high quality 100% PAO synthetic technology base stocks in combination with an unique additive technology to achieve the following performance:

- Long drain intervals
- High protection against deposits and "sludge" formation
- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High viscosity index

## Performance Levels

API SN/CF    ACEA A3/B4    MB 229.5    VW 502.00/505.00    Renault RN 0710  
PSA B71 2296    GM-LL-B-025

Test Item	Typical Spec.	Typical Result
SAE Grade		5W40
Density @15°C	kg/m <sup>3</sup>	853
Kin. Viscosity @40°C	mm <sup>2</sup> /s	87
Kin. Viscosity @100°C	mm <sup>2</sup> /s	14.3
Viscosity Index		171
Viscosity CCS @-30°, max.	cP	6600
Flash Point COC	°C	>201
Pour Point	°C	-39
Total Base Number	mgKOH/g	10.2
Sulphated Ash	%Wt	1.09

\*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

