



SIGMA 900 4T 10W60



German Quality

MUXX OIL GmbH
Hauptstr. 117, 10827 Berlin,
Deutschland.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- SIGMA 900 4T 10W60 is manufactured from high quality base oil with fully synthetic Group IV PAO and unique Syn Ester base stock which meet the latest version of JASO MA2 performance additive system. It is designed primarily for four stroke wet clutch motorcycles.
- SIGMA 900 4T 10W60 will keep engine components clean with smooth excellent clutch shifting, as well as provide protection against wear, rust and corrosion. This grade is ideal for most types of small engines which require the MA2 performance.
- SIGMA 900 4T 10W60 is recommended for four stroke small engine with wet clutch motorcycles.
- SIGMA 900 4T 10W60 viscosity is the ideal range for the daily-use motorcycles which require quick oil flow performance in certain weather conditions. It can be used for most OEM manufactures without any emission requirement

Performance Levels

API SN JASO MA2

Test Item	Typical Spec.	Typical Result
Density at 15°C	Report	0.862
Kinematic Viscosity at 100°C, cSt	Min. 21.9	22.85
Kinematic Viscosity at 40°C, cSt	Report	158.06
Viscosity Index	Min. 170	174
Flash Point (Open)°C	Min. 200	235
TBN, mg/KOH/g	Min. 8.0	8.2
Pour Point, °C	Max. -21	-39
Color	Report	2.0
CCS-25°C	Max. 7000	5800

*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

