



# 300 4T 15W50



German Quality

MUXX OIL GmbH  
15 Frankenhäuser St., 12249 Berlin,  
Germany.  
Office: +49 (0)30 61633942  
Website: [www.muxxlube.de](http://www.muxxlube.de)  
E-Mail: [service@muxxlube.com](mailto:service@muxxlube.com)

## Description

- C 300 4T 15W50 is manufactured from high quality base oil with partial fully synthetic VHVI base oil and an advanced JASO MA performance additive system. It is designed primarily for four stroke wet clutch motorcycles.
- C 300 4T 15W50 will keep engine components clean with smooth excellent clutch shifting, as well as provide protection against wear, rust and corrosion. This grade is ideal for most types of small engines which require the MA performance.
- C 300 4T 15W50 is recommended for four stroke small engine with wet clutch motorcycles. C 300 4T 15W50 viscosity range is the ideal range for the daily-use motorcycles which require quick oil flow performance in certain weather conditions. It can be used for most OEM manufactures without any emission requirement.

## Performance Levels

API SN JASO MA

Test Item	Typical Spec.	Typical Result
SAE Grade		15W50
Density @15°C	kg/m <sup>3</sup>	863
Kin. Viscosity @40°C	mm <sup>2</sup> /s	141.93
Kin. Viscosity @100°C	mm <sup>2</sup> /s	19.12
Viscosity Index		154
Viscosity CCS @-20°	cP	6100
Flash Point COC	°C	234
Pour Point	°C	-35
Total Base Number	mgKOH/g	7.0
Color		L2.5

\*The Above Test Result is subject for change and for reference only

