



100 4T 15W40



German Quality

MUXX OIL GmbH
15 Frankenhäuser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- E 100 4T 15W40 is manufactured from high quality mineral oil and an advanced additive system. It is designed primarily for petrol engines, but may also be used in older versions of diesel engines. E 100 4T 15W40 will keep engine components clean and deposit-free, as well as provide protection against wear, rust and corrosion. This grade is ideal for engines which start to suffer from high consumption or low oil pressure.
- E 100 4T 15W40 is an ideal choice for older cars with high mileage. This grade has been proven on the track and will provide impressive oil pressure and protection under heavy load and high temperatures. E 100 4T 15W40 is also suitable for older engines that have been rebuilt and a full-flow cartridge filter has been added.

Performance Levels

API SL JASO MA

Test Item	Typical Spec.	Typical Result
SAE Grade		15W40
Density @15°C	kg/m ³	868
Kin. Viscosity @40°C	mm ² /s	110.63
Kin. Viscosity @100°C	mm ² /s	14.45
Viscosity Index		133
Viscosity CCS @-20°	cP	6200
Flash Point COC	°C	230
Pour Point	°C	-39
Total Base Number	mgKOH/g	6.1
Color		2.0

*The Above Test Result is subject for change and for reference only

