



100 4T 20W50



German Quality

MUXX OIL GmbH
15 Frankenhäuser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- E 100 4T 20W50 is manufactured from high quality hydro-cracking mineral oil and an advanced additive system. It is designed primarily for four stroke petrol small engines with the extra friction modifier. E 100 4T 20W50 will keep engine components clean and deposit-free, as well as provide protection against wear, rust and corrosion. This grade is ideal for engines which start to suffer from high consumption or low oil pressure.
- E 100 4T 20W50 is recommended for most types of four stroke petrol small engines, especially for the scooters or motorbikes. E 100 4T 20W50 viscosity is the ideal range for the daily-use vehicles which require quick oil flow performance in certain weather conditions.

Performance Levels

API SL JASO MA

Test Item	Typical Spec.	Typical Result
SAE Grade		20W50
Density @15°C	kg/m ³	873
Kin. Viscosity @40°C	mm ² /s	125.01
Kin. Viscosity @100°C	mm ² /s	16.5
Viscosity Index		142
Viscosity CCS @-15°	cP	7955
Flash Point COC	°C	236
Pour Point	°C	-24
Total Base Number	mgKOH/g	6.1
Color		L1.5

*The Above Test Result is subject for change and for reference only

