



German Quality

MUXX OIL GmbH
 15 Frankenhauser St., 12249 Berlin,
 Germany.
 Office: +49 (0)30 61633942
 Website: www.muxxlube.de
 E-Mail: service@muxxlube.com

500 4T 10W40

Description

- F 500 4T 10W40 is manufactured from high quality base oil VHVI hydro-treated base stock with unique Ester technology. This product meets the JASO MA2 friction test that is designed primarily for four stroke wet clutch motorcycles.
- F 500 4T 10W40 will keep engine components clean with smooth excellent clutch shifting, and provide protection against wear, rust and corrosion. This grade is ideal for most types of small engines which require the MA2 performance.
- F 500 4T 10W40 is recommended for four stroke small engine with wet clutch motorcycles.
- F 500 4T 10W40 viscosity range is the ideal range for the daily-use motorcycles which require quick oil flow performance in certain weather conditions. It can be used for most OEM manufactures without any emission requirement.

Performance Levels

API SN JASO MA2

Test Item	Typical Spec.	Typical Result
SAE Grade		10W40
Density @15°C	kg/m ³	851
Kin. Viscosity @40°C	mm ² /s	91.82
Kin. Viscosity @100°C	mm ² /s	15.01
Viscosity Index		172
Viscosity CCS @-25°.	cP	5980
Flash Point COC	°C	230
Pour Point	°C	-36
Total Base Number	mgKOH/g	6.8
Color		Blue

*The Above Test Result is subject for change and for reference only

