



600 FE 5W20



German Quality

MUXX OIL GmbH
Hauptstr. 117, 10827 Berlin,
Deutschland.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- D 600 FE 5W20 is 100% manufactured from VHVI base oils and an advanced additive system and is designed primarily for petrol engine. This product enhanced oil flow give essential protection during engines start up.
- D 600 FE 5W20 also employs the low ash additive technology which meet the requirement of the GPF system as well as the LSPI engines.
- D 600 FE 5W20 is recommended for the latest petroleum engines where fitted with turbo and supercharged system.
- D 600 FE 5W20 can be used for most of modern engine design as well as where the API SP and API SN Plus standard requirement.

Performance Levels

API SP/SN Plus ILSAC GF-6A ACEA C5 Dexos 2 Gen.II Fiat 9.55535-CR1 Ford WSS-M2C948-B Ford WSS-M2C960-A
Ford WSS-M2C945-B1 Jaguar Land Rover STJLR.03.5004 Chrysler MS-6395

Test Item	Typical Spec.	Typical Result
SAE Grade		5W20
Density @15°C	Report	858
Kin. Viscosity @40°C	Report	47.52
Kin. Viscosity @100°C	7.0-9.3	8.45
Viscosity Index	Min. 140	156
Viscosity CCS @-30°, max.	Max. 6600	5810
Flash Point COC	Min. 200	215
Pour Point	Max. -21	-42
Total Base Number	Min. 7.0	7.5

*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

