



800 V 0W30



German Quality

MUXX OIL GmbH
Hauptstr. 117, 10827 Berlin,
Deutschland.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- R 800 V 0W30 is a complete fully synthetic advanced lubricant, designed for use in the latest technology engines, including those fitted with DPF after treatment devices.
- R 800 V 0W30 employs PAO Group IV and Group V which designed by exclusive additive formulation which meets the standard of VW 504/507 specifications.
- R 800 V 0W30 is recommended for the latest petrol and diesel engines, including Turbo-Charged versions and those fitted with exhaust gas after treatment devices such as DPF, Catalytic Converts and R 800 V 0W30 may be used in all VGA vehicles employing fixed service or long life service maintenance schedules where the use of engine oils meeting the requirements of VW 504.00/507.00.

Performance Levels

API SN ACEA C3 MB 229.51/229.52 BMW LL-04 Porsche C30 VW 504/507 GM Dexos 2

Test Item	Typical Spec.	Typical Result
SAE Grade		0W30
Density @15°C	Report	853
Kin. Viscosity @40°C	Report	61.13
Kin. Viscosity @100°C	9.5-12.3	11.25
Viscosity Index	Min. 160	181
Viscosity CCS @-35°, max.	Max. 6200	5700
Flash Point COC	Min. 200	230
Pour Point	Max. -30	-45
Total Base Number	Min. 8.0	8.2
Sulphated Ash	Max. 0.8	0.8

*The Above Test Result is subject for change and for reference only



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

