

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MU

MUXX ÖL

Deutschland Schmierstoffe



German Quality

MUXX OIL GmbH
Hauptstr. 117, 10827 Berlin,
Deutschland.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- F 500 4T 15W50 is manufactured from high quality base oil XHVI hydro-treated base stock with unique Ester technology. This product meets the JASO MA2 friction test that is designed primarily for four stroke wet clutch motorcycles.
- F 500 4T 15W50 will keep engine components clean with smooth excellent clutch shifting, and provide protection against wear, rust and corrosion. This grade is ideal for most types of small engines which require the MA2 performance.
- F 500 4T 15W50 is recommended for four stroke small engine with wet clutch motorcycles.
- F 500 4T 15W50 viscosity range is the ideal range for the daily-use motorcycles which require quick oil flow performance in certain weather conditions. It can be used for most OEM manufactures without any emission requirement.

Performance Levels

API SN JASO MA2

Test Item	Typical Spec.	Typical Result
Density at 15°C	Report	0.862
Kinematic Viscosity at 100 °C , cSt	17.0-21.0	18.95
Kinematic Viscosity at 40 °C , cSt	Report	137.50
Viscosity Index	Min. 150	157
Flash Point (Open)°C	Min. 200	232
TBN, mg/KOH/g	Min. 7.5	8.2
Pour Point, °C	Max. -12	-33
Color	Report	L2.5
CCS-20°C	Max. 7000	5800

*The Above Test Result is subject for change and for reference only


muxxlube.de